

Scheduled Maintenance: We want to alert you of planned maintenance that will include some downtime on 23 and 30 July 2022. Between the hours of 9AM and 1PM ET on each of these dates, users will experience approximately two hours of downtime and will be unable to access the IEEE Xplore Digital Library platform.

IEEE.org IEEE Xplore IEEE SA IEEE Spectrum More Sites

Cart Create Personal Account Sign In



Browse My Settings Help

Access provided by: Centurion university of technology and management

Sign Out

Access provided by: Centurion university of technology and management

Sign Out

All

ISBN: 978-1-6654-2525-4



ADVANCED SEARCH

Back to Results

Conferences > 2022 International Conference...

Wide Band Conformal Coplanar Benz Shaped Circular Ring Antenna for C and X Band Applications

Publisher: IEEE

Cite This

PDF

<< Results

L.B Prasad ; Harish Ch. Mohanta ; K. P Vinay All Authors

Dept. of ECE, Centurion University of Technology & Management, Odisha, India

6 Full Text Views



Alerts

Manage Content Alerts

Add to Citation Alerts

More Like This

An ultrawideband coplanar waveguide-fed tapered ring slot antenna
IEEE Transactions on Antennas and Propagation
Published: 2006

Frequency Selective Surface Effects on a Coplanar Waveguide Feedline in Fabry-Perot Cavity Antenna Systems
IEEE Antennas and Wireless Propagation Letters
Published: 2018

Show More

Abstract

Download PDF

Document Sections

I. Introduction

Abstract:A Conformal Coplanar Benz Shaped Circular Ring (CBSCR) patch antenna operates in the upper C-band and X-band region with compact structure is presented in this work. Patc... **View more**

II. Antenna Geometry and Design

Metadata

III. Simulation Result and Analysis

Abstract: A Conformal Coplanar Benz Shaped Circular Ring (CBSCR) patch antenna operates in the upper C-band and X-band region with compact structure is presented in this work. Patch is etched on a polyimide substrate with dielectric constant 3.5 and height 0.8mm. The proposed ring antenna has compact size of 20x20 mm² is feed with coplanar waveguide which provides wide impedance bandwidth of 4.34GHz from 6.95GHz to 11. 29GHz with resonant frequency of 9.08GHz. CST Microwave Studio is used to design and simulate the proposed ring patch antenna. The simulation results show the return loss of -12dB,

IV. Conclusion

Authors